

# REPUBLIC OF THE PHILIPPINES

## EDICT OF GOVERNMENT

In order to promote public education and public safety, equal justice for all, a better informed citizenry, the rule of law, world trade and world peace, this legal document is hereby made available on a noncommercial basis, as it is the right of all humans to know and speak the laws that govern them.

PNS/PAES 148 (2010) (English): Agricultural machinery - Field cultivator - Methods of Test



BLANK PAGE



# PHILIPPINE NATIONAL STANDARD

PNS/PAES 148:2010  
(PAES published 2010)  
ICS 65.060.01

---

**Agricultural machinery – Field cultivator –  
Methods of Test**

JUN 09 2010



**BUREAU OF PRODUCT STANDARDS**

Member to the International Organization for Standardization (ISO)  
Standards and Conformance Portal: [www.bps.dti.gov.ph](http://www.bps.dti.gov.ph)

**National Foreword**

This Philippine Agricultural Engineering Standards PAES 148:2010, Agricultural machinery – Field cultivator – Methods of Test was approved for adoption as Philippine National Standard by the Bureau of Product Standards upon the recommendation of the Agricultural Machinery Testing and Evaluation Center (AMTEC) and the Philippine Council for Agriculture, Forestry and Natural Resources Research and Development of the Department of Science and Technology (PCARRD-DOST).

## **Foreword**

The formulation of this national standard was initiated by the Agricultural Machinery Testing and Evaluation Center (AMTEC) under the project entitled “Development of Standards for Agricultural Production and Postharvest Machinery” funded by the Philippine Council for Agriculture, Forestry and Natural Resources Research and Development - Department of Science and Technology (PCARRD-DOST).

This standard has been technically prepared in accordance with BPS Directives Part 3:2003 – Rules for the Structure and Drafting of International Standards.

The word “shall” is used to indicate mandatory requirements to conform to the standard.

The word “should” is used to indicate that among several possibilities one is recommended as particularly suitable without mentioning or excluding others.

In the preparation of this standard, the following documents/publications were considered:

Alberta Farm Machinery Research Centre. 1991. Evaluation report 268.

American Society of Agricultural Engineers S414.1 – Terminology and Definitions for Agricultural Tillage Implements

ASAE EP496.2 - Agricultural Machinery Management

ASAE D497.4 - Agricultural Machinery Management Data

Regional Network for Agricultural Machinery. 1983. Test codes and procedures for farm machinery. Technical Series No.12. Economic and Social Commission for Asia and the Pacific.

Philippine Agricultural Engineering Standard 106:2000 – Agricultural Machinery – Soil Tillage and Equipment – Terminology

United States Patents 4195697

United States Patents 5161622

Grubinger, V. *Cultivation Equipment For Weed Control: Pros, Cons And Sources*. University of Vermont Extension.

<http://ag.arizona.edu/crops/equipment/agmachinerymgt.html>

<http://www.sare.org/publications/steel/glossary.htm>

<b>CONTENTS</b>	<b>Page</b>
<b>1</b> Scope	3
<b>2</b> References	3
<b>3</b> Definitions	3
<b>4</b> General Conditions for Test and Inspection	6
<b>4.1</b> Role of the manufacturer/dealer	6
<b>4.2</b> Role of the operator	6
<b>4.3</b> Test site conditions	6
<b>4.4</b> Test instruments/equipment	7
<b>4.5</b> Tractor to be used	7
<b>4.6</b> Termination of test for the field cultivator	7
<b>5</b> Test and Inspection	7
<b>5.1</b> Verification of the manufacturer's technical data and information	7
<b>5.2</b> Performance test	7
<b>5.3</b> Test trial	10
<b>6</b> Test Report	10

#### *ANNEXES*

<b>A</b> Suggested Minimum List of Test Equipment	12
<b>B</b> Specifications of Field Cultivator	13
<b>C</b> Performance Test Data Sheet	15
<b>D</b> Formula Used During Calculation and Testing	17

---

**Agricultural Machinery – Field Cultivator – Methods of Test**

---

**1 Scope**

This standard specifies the methods of test and inspection for a field cultivator. Specifically, it shall be used to:

- 1.1 verify the mechanism, dimensions, materials, accessories and workmanship of the field cultivator and the list of specifications submitted by the manufacturer;
- 1.2 determine the performance of the equipment; and,
- 1.3 report the results of the tests.

**2 References**

The following normative documents contain provisions, which through reference in this text constitute provisions of this National Standard:

**PAES 147:2010**      Agricultural Machinery - Field Cultivator – Specifications

**3 Definitions**

For the purpose of this standard, the definitions given in PAES 147 and the following shall apply:

**3.1****draft**

total force parallel to the direction of travel required to move the implement

**3.2****drawbar power**

power requirement of an implement being towed or pushed

**3.3****effective field capacity**

function of field speed, operating width and field efficiency expressed in hectares per hour

**3.4****field efficiency**

ratio between the productivity of a machine under field conditions and the theoretical maximum productivity

### 3.5


#### **implement**

any agricultural tool mounted on the tractor

### 3.6

#### **implement width**

horizontal distance perpendicular to the direction of travel between the outermost edges of the implement (Fig. 1)




**Figure 1. Implement width**

### 3.7

#### **nose angle**

angle formed by the edges of the sweep (Fig. 2)




**Figure 2. Nose angle**

### 3.8

#### **operating width**

horizontal distance perpendicular to the direction of travel within which an implement performs its intended function; distance between the outermost shanks of the field cultivator (Fig. 3)






**Figure 3. Operating width**

### 3.9

#### **stem angle**

angle formed by the shank or the shovel relative to the ground surface or to its base, respectively (Fig. 4)



**Figure 4. Stem angle**

### 3.10

#### **theoretical field capacity**

function of speed and operating width expressed in hectares per hour

### 3.11


#### **transport height**

overall height of the implement measured from the topmost point to its lowest point (Fig. 5)


### 3.12

#### **transport length**

overall length of the implement measured from the terminal point of the implement to the mounting point (Fig. 5)



**Figure 5a. Transport height and length (four-wheel driven type)**



**Figure 5b. Transport height and length (two-wheel driven type)**

### 3.12

#### **wheel slip**

reduction on the distance traveled by the tractor due to the attached implement

## **4 General Conditions for Test and Inspection**

### **4.1 Role of manufacturer/dealer**

The manufacturer shall submit the operator's manual of the field cultivator and shall abide by the terms and conditions set forth by an official testing agency.

### **4.2 Role of the operator**

An officially designated operator shall be skilled and shall be able to demonstrate, operate, adjust and make repairs related to the operation of the equipment.

### **4.3 Test site conditions**

The field cultivator shall be tested through actual cultivation of the soil. The field shall have ample space to allow turns in headland. The size of the field shall not be

less than 1000 m<sup>2</sup> and shall be rectangular in shape, with sides in ratio of 2:1 as much as possible.

#### **4.4 Test instruments/equipment**

The suggested list of minimum test equipment needed to carry out the field cultivator test is shown in Annex A.

#### **4.5 Tractor to be used**

The tractor to be used to conduct the test shall be compatible with the field cultivator in accordance with the manufacturer's specification of required power.

#### **4.6 Termination of test for field cultivator**

If during the test, the field cultivator encounters major component breakdown or malfunction, the test engineer shall terminate the test.

### **5 Test and Inspection**

#### **5.1 Verification of the manufacturer's technical data and information**

This inspection is carried out to verify the mechanism, dimensions, materials and accessories of the field cultivator in comparison with the list of manufacturer's technical data and information. All data shall be recorded in Annex B.

#### **5.2 Performance test**

**5.2.1** This is carried out to obtain actual data on overall performance of the equipment.


##### **5.2.2 Measurement of initial data**

Initial data, such as field area, soil type and soil moisture content, shall be obtained and recorded in Annex C before the test operation.

##### **5.2.3 Field performance test**

**5.2.3.1** The field cultivator shall be tested at the recommended depth settings of the manufacturer. The actual operating depth shall be noted and shall be compared with the theoretical operating depth.

**5.2.3.2** The tractor speed shall be determined according to the recommended depth setting. This can be done by recording the time required for the tractor to travel a 20 m distance in the field (Fig. 6).



**Figure 6. Points for speed test**

**5.2.3.3** The total test time shall be obtained by acquiring the total time to finish cultivating the test field. Non-productive time (e.g. headland turns) shall be recorded. Productive time shall be obtained by deducting the non-productive time from the total test time.


**5.2.3.4** The fuel consumed by the tractor shall be obtained. This can be done by measuring the volume of fuel refilled after the test. The tank shall be filled to full capacity before and after each trial.

**5.2.3.5** The operating width shall be obtained by measuring the distance between the outermost shanks and shall be noted.

**5.2.3.6** Field efficiency, effective field capacity and drawbar power requirements of the implement shall be obtained using the formula in Annex D.

#### **5.2.3.7 Determination of draft**


A spring, hydraulic or strain-gauge type dynamometer shall be attached to the front of the tractor on which the implement is mounted. Another auxiliary tractor shall pull the implement-mounted tractor through the dynamometer in neutral gear but with the implement in its operating position (Fig. 7). The draft in the measured distance of 20 m as well as the time it takes to traverse it shall be recorded. On the same field, the draft in the same distance shall be recorded while the implement is lifted above the ground. The difference in the draft readings shall yield the draft of the implement.



**Figure 7. Position of tractors for draft measurement**

#### **5.2.3.8 Test for uniformity of depth of cut**


**5.2.3.8.1** Two points in the field passed shall be marked using pegs (points A and B). The distance between these points shall be 20 m. Every two meters, a marking peg shall be placed (Fig. 8).



**Figure 8. Soil strips marking for operating depth analysis**

**5.2.3.8.2** The operating depth of the field cultivator shall be set. The field cultivator shall be operated along the marked strips (Fig. 8). These strips of soil shall be observed.


**5.2.3.8.3** The depth of cut for each strip shall be measured and shall be recorded. The mean depth shall be computed and shall be recorded (Fig. 9).



**Figure 9. Depth of cut**

**5.2.3.8.4** The percent error for the mean depth shall be computed using the formula in Annex D.

**5.2.3.8.5** The percentage of wheel slip shall be obtained by recording the difference of the distance traveled without load and the distance traveled with the implement attached. A mark shall be placed on the wheel of the tractor (Fig. 10). The tractor shall be allowed to move forward up to 10 revolutions of the marked wheel under no load (A). The distance shall be measured and recorded. On the same surface, the tractor shall be allowed to move forward with the implement attached. After same number of revolutions, the distance traveled shall be measured and recorded (B). The percentage of wheel slip shall then be computed using the formula in Annex D.



**Figure 10. Measuring of wheel slip**

**5.2.3.9** Condition of field cultivator after test shall be compared to its initial condition.

**5.2.3.10** Welded parts shall be inspected.

**5.2.3.11** Loosened bolts shall be noted.

**5.2.3.12** All data shall be recorded in Annex C.

### **5.3 Test trial**

There shall be at least three (3) trials in conducting the test.

## **6 Test Report**

The test report shall include the following information in the order given:

**6.1** Title

**6.2** Summary

**6.3** Purpose and Scope of Test

**6.4** Methods of Test

**6.5** Description of the Machine

Table 1 – Machine Specifications

**6.6** Results and Discussions

**6.7** Observations (include pictures)

Table 2 –Performance test data

**6.8** Name(s), signature(s) and designation(s) of test engineer(s)

## Annex A

### Suggested Minimum List of Test Equipment

Items		Quantity
A.1.	timer accuracy: 0.10 s	1
A. 2	steel tapes length: 5 m; 50 m	2
A.3	weighing scale capacity, 1000 kg	1
A.4	fuel consumption	
	graduated cylinder capacity, 1000 mL	1
A.5	four-wheel tractor	2
A.6	soil analysis	
	soil test kit	1
	oven	1
A.7	marking pegs	4
A.8	marking tape	1
A.9	calculations	
	scientific calculator	1
A.10	draft measurement	
	spring, hydraulic or strain-gauge type dynamometer	1



**Annex B**  
(informative)

**Specifications of Field Cultivator**

Name of Applicant/ Distributor: \_\_\_\_\_

Address: \_\_\_\_\_

Tel No: \_\_\_\_\_

**GENERAL INFORMATION**

Name of Manufacturer: \_\_\_\_\_

Make: \_\_\_\_\_

Classification: \_\_\_\_\_

Serial No: \_\_\_\_\_ Brand/Model: \_\_\_\_\_

Production date of field cultivator to be tested: \_\_\_\_\_

Testing Agency: \_\_\_\_\_ Test Engineer: \_\_\_\_\_

Date of Test: \_\_\_\_\_ Location of Test: \_\_\_\_\_

**Items to be inspected**

ITEMS	Manufacturer's Specification	Verification by the Testing agency
<b>B.1 overall dimensions</b>		
B.1.1 transport height, mm		
B.1.2 transport length, mm		
B.1.3 implement width, mm		
B.1.4 weight, kg		
B.1.5 operating width, mm		
<b>B.2 main frame</b>		
B.2.1 material		
B.2.2 dimensions, mm		
<b>B.3 shank assembly</b>		
<b>B.3.1 shank protection mechanism</b>		
B.3.1.1 material		
<b>B.3.2 shank</b>		
B.3.2.1 material		
B.3.2.2 dimensions, mm		
B.3.2.3 ground clearance, mm		
B.3.2.4 stem angle, degrees		
B.3.2.5 spacing, mm		
B.3.2.6 type		
B.3.2.7 number of shanks		
<b>B.3.3 shovel</b>		
B.3.3.1 material		
B.3.3.2 type		
B.3.3.3 dimensions, mm		
B.3.3.4 stem angle, degrees (for sweeps)		
B.3.3.5 nose angle, degrees (for sweeps)		

ITEMS	Manufacturer's Specification	Verification by the Testing agency
<b>B.4 transverse tool bar</b>		
<b>B.4.1</b> material		
<b>B.4.2</b> dimensions, mm		
<b>B.4.3</b> number of shanks		
<b>B.5 gauge wheels (if present)</b>		
<b>B.5.1</b> diameter, mm		
<b>B.5.2</b> adjustments		
<b>B.6 mounting details</b>		
<b>B.7 cylinder (if present)</b>		
<b>B.7.1</b> type		
<b>B.7.2</b> capacity, Pa		
<b>B.7.3</b> bore, mm		
<b>B.7.4</b> stroke, mm		
<b>B.8 tractor required</b>		
<b>B.8.1</b> type		
<b>B.8.2</b> recommended traveling speed, kph		
<b>B.8.3</b> engine power, kW		

## ANNEX C

### Performance Test Data Sheet

#### Items to be measured and Inspected

<b>C.1 Test field conditions</b>				<b>Remarks</b>			
<b>C.1.1</b> area of field, m <sup>2</sup>							
<b>C.1.2</b> soil type (clay, clay loam, sandy, etc.)							
<b>C.1.3</b> soil texture (fine, medium, coarse)							
<b>C.1.4</b> soil moisture content (% d.b.)							

<b>C.2 Field performance</b>									
<b>C.2.1 Actual operating depth, mm</b>									
<b>Manufacturer's recommended depth setting, mm</b>	<b>Trials</b>								
	<b>1</b>		<b>2</b>		<b>3</b>		<b>average</b>		
<b>C.2.2 Tractor speed, kph</b>									
<b>C.2.3 Operating time, h</b>	<b>Trials</b>								
	<b>1</b>		<b>2</b>		<b>3</b>		<b>average</b>		
	Test time	Non-productive	Test time	Non-prod.	Test time	Non-prod.	Test time	Non-prod.	Productive time
<b>C.2.4 Fuel consumed, mL</b>	<b>Trials</b>								
	<b>1</b>		<b>2</b>		<b>3</b>		<b>average</b>		
<b>C.2.5 Field efficiency, %</b>									
<b>C.2.6 Effective field capacity, ha/h</b>									
<b>C.2.7 Draft, N</b>									
<b>C.2.8 Drawbar power, kW</b>									

[illegible]

C.3 Other observations	Remarks
C.3.1 ease of mounting/dismounting *	
C.3.2 accessibility of grease points *	
C.3.3 number of shanks deformed after test	
C.3.4 number of shovels detached after test	
C.3.5 cracks on welded parts	
C.3.6 detached welded parts	
C.3.7 loosened bolts	
C.3.8 miscellaneous:	

\* rating:

1 – very good  
2 – good  
3 – satisfactory

4 – poor  
5 – very poor

## ANNEX D

### Formula Used During Calculation and Testing

#### D.1. Drawbar power

$$P = \frac{D \times S}{3.6}$$

where:

$P$  drawbar power required for the implement, kW

$D$  draft force required to move the implement, kN

$S$  speed of tractor, kph

#### D.2. Effective field capacity

$$C = \frac{60 E}{T}$$

where:

$C$  effective field capacity, ha/h

$E$  effective area accomplished, m<sup>2</sup>

$T$  operating time, h

#### D.3. Field efficiency

$$Eff = \frac{C}{C_o} \times 100$$

where:

$Eff$  field efficiency, %

$C$  effective field capacity, m<sup>2</sup>/h

$C_o$  theoretical field capacity, m<sup>2</sup>/h

#### D.4. Effective area accomplished

$$E = wD$$

where:

$E$	effective area accomplished, m <sup>2</sup>
$w$	actual working width, m
$D$	total distance traveled, m

#### D.5. Total distance traveled

$$D = \frac{A}{S}$$

where:

$D$	total distance traveled, m
$A$	area of plot, m <sup>2</sup>
$S$	average swath or width of cut, m

#### D.6. Average swath or width of cut

$$S = \frac{W}{2N}$$

where:

$S$	average swath or width of cut, m
$W$	width of plot, m
$N$	number of trips per round

#### D.7. Percent error for mean depth

$$\% \text{ error} = \frac{|D_m - D_p|}{D_p} \times 100$$

where:

$\% \text{ error}$	percent error, %
$D_m$	mean depth, mm
$D_p$	theoretical depth, mm

#### D.8. Percentage of wheel slip

$$\% W.S. = \frac{A-B}{A} \times 100$$

where:

$\% W.S.$	percent of wheel slip, %
$A$	distance traveled by the tractor under no load after a given number of revolution, m
$B$	distance traveled by the tractor with implement attached after a given number of revolution, m

#### D.9. Theoretical Field Capacity

$$C_o = w \times S$$

where:

$C_o$	theoretical field capacity, ha/h
$w$	actual working width, m
$S$	speed of tractor, m/h

## **Philippine Agricultural Engineering Standards**

AMTEC-UPLB – PCARRD Project: “Development of Standards for Agricultural Production and Postharvest Machinery”

### **Technical Committee 1. Production Machinery**

Chairman: Engr. Joel R. Panagsagan  
Agricultural Machinery Manufacturers and Distributors Association  
(AMMDA), Inc.

Members: Dr. Caesar Joventino M. Tado  
Philippine Rice Research Institute (PhilRice)

Engr. Francia M. Macalintal  
National Agricultural and Fishery Council (NAFC)  
Department of Agriculture

Engr. Julieto T. Uriarte  
Metal Industry Research and Development Center (MIRDC)  
Department of Science and Technology

Engr. Angelito V. Angeles  
Philippine Society of Agricultural Engineers (PSAE)

### **Technical Committee 2. Postharvest Machinery**

Chairman: Engr. George Q. Canapi  
Agricultural Machinery Manufacturers and Distributors Association  
(AMMDA), Inc.

Members: Engr. Dionisio C. Coronel, Sr.  
National Food Authority (NFA)  
Department of Agriculture

Engr. Reynaldo P. Gregorio  
Bureau of Postharvest Research and Extension (BPRE)  
Department of Agriculture

Engr. Jose B. Ferrer  
Metal Industry Research and Development Center (MIRDC)  
Department of Science and Technology

Dr. Elmer D. Castillo  
Philippine Society of Agricultural Engineers (PSAE)